

## Implementation examples Mediastore

### API operations

//The standard API Request URL structure to get the binary image data of a product looks like this:

`https://{{Host}}/api/products/{{id}}/{{angle}}/image`

where host = mediastore.tradesolution.no/

The request to the standard API needs to include a Basic authorization header with an encoded username and password.

C# (Restsharp) implementation example:

```
Convert.ToBase64String(Encoding.ASCII.GetBytes(userInfo.Id + ":" + userInfo.Password))
=> c31zdGVtYnJ1a2VyQFRyYWRlc29sdXRpb24ubm86RGFydGhWYpWlcjEyMw==

var client = new RestClient
("https://mediastore.tradesolution.no/api/products/123456789/1C/image");
    var request = new RestRequest(Method.GET);
    request.AddHeader("cache-control", "no-cache");
    request.AddHeader("authorization", "Basic
c31zdGVtYnJ1a2VyQFRyYWRlc29sdXRpb24ubm86RGFydGhWYpWlcjEyMw==");
    IRestResponse response = client.Execute(request);
```

cURL example:

```
curl -X GET -H "Authorization: Basic
c31zdGVtYnJ1a2VyQFRyYWRlc29sdXRpb24ubm86RGFydGhWYpWlcjEyMw==" -H "Cache-Control: no-
cache" "https://mediastore.tradesolution.no/api/products/123456789/1C/image"
```

### CDN Operations

//The CDN Request URL structure to get the binary image data of a product looks like this:

`https://{{CDNHost}}/api/products/{{userHash}}/{{id}}/{{angle}}/image`

where the CDNHost = Tradesolutions.akamaized.net

The userHash value is returned by the API operation /products/getUserHash. Any image metadata request made to the standard API will also reveal the userHash for the calling user in the CDNUrl returned. The userHash is different for every user, but does not change for a particular user.

The request needs some request headers:

```
Cache-control: no-cache  
Host: tradesolutions.akamaized.net  
__token__ (Value to be used is to be taken from the /products/gettoken operation)
```

C# (Restsharp) example:

```
var client = new  
RestClient("https://tradesolutions.akamaized.net/api/products/dsf7239sdfs98723cds/123  
456789/1C/image");  
var request = new RestRequest(Method.GET);  
  
request.AddHeader("cache-control", "no-cache");  
  
request.AddHeader("__token__", "exp=1476265823~acl=/*/dsf7239sdfs98723cds  
/*!/*~hmac=a96d6f4853079197f9f0ba523f591c003c7e2058a81674eece9c3739fcfea53");  
  
request.AddHeader("host", "tradesolutions.akamaized.net");  
  
IRestResponse response = client.Execute(request);
```

cURL example:

```
curl -X GET -H "host: tradesolutions.akamaized.net" -H "__token__:  
exp=1476265823~acl=/*/dsf7239sdfs98723cds/*!/*~hmac=a96d6f4853079197f9f0ba523f591c003  
c7e2058a81674eece9c3739fcfea53" -H "Cache-Control: no-cache"  
"https://tradesolutions.akamaized.net/api/products/8076800195132/1C/image"
```